

OVERVIEW

AUTOMATION



MILLENIUM 3
MILLENIUM 3 ACCESSORIES

em4

ABOUT CROUZET

Supported by an experienced technical team, Crouzet is a pioneer in the simplification of programming. The brand offers the easiest-to-use and most adaptable alternative automation solution for specialized and demanding needs.

Crouzet is a brand of InnoVista Sensors™.



InnoVista Sensors™ is a worldwide industrial specialist of sensors, controllers and actuators for automated systems.

Through its brands, Crouzet and Syston Donner Inertial, InnoVista Sensors™ offers a wide range of reliable, efficient and customizable components dedicated to the Aerospace & Defense, Transportation and Industrial markets and segments.

Thanks to the recognized expertise of its teams and a strong innovation policy, InnoVista Sensors™ brings performance enhancing solutions to its customers worldwide.

InnoVista Sensors™: your trusted partner of choice to face industrial challenges of today and tomorrow.

www.innovistasensors.com


Designs & Manufactures



Sensors



Controls



Actuators

For



Aerospace
& Defense



Transportation



Industry

ADAPTATION WHEEL

To meet market expectations and provide customers with the right solutions within the shortest timeframes, Crouzet has structured its processes around different types of products: standard products, adapted products and products specially developed for a customer. Introducing the adaptation wheel...



1 STANDARD COMPONENTS

A complete range of logic controllers immediately available to create your automation application.

2 COMPONENTS WITH ADDED VALUE

Standard products complemented by factory-mounted auxiliaries or accessories (connectors, wire outputs, cables, etc.) in order to assist integration into your equipment, simplify your logistics and maximize the reliability of your installation.

3 ADAPTED PRODUCTS

Defined jointly with our technical sales teams, these adapted products offer the exact performance and functions you need for your application.

4 SPECIFIC PRODUCTS

All our design and industrialization expertise in automation systems at your service, to design and create specific products dedicated to your application.

WHICH SOLUTION DO YOU NEED?

em4 is more than just a nano-PLC: it is a leading edge device supported by best-in-class tools that enables you to create and implement the smartest automation applications with **em4** soft.

NANO-PLC

em4 remote

The first all-in-one solution to bring your application into the Internet of Things

Remotely manage your equipment and application programs



Remotely display or control data values with a web platform



Periodically receive data log reports by email or FTP



Receive and manage notifications when an event occurs in your application

em4 alert

The PLC which sends alerts via SMS, stores data logs in .csv (Excel) and sends them by email or FTP



Remotely display or control data values with SMS



Receive an SMS or an email when an event occurs in your application

em4 local/ethernet

The **em4** for stand alone use or local area network

Embedded configurable 0-10V/4-20mA accurate analog inputs



Powerful & up to 24 analog inputs included



Modbus RS485 slave interface option for connection Touch HMI



LOGIC CONTROLLER

Smart Expandable

Offers a large variety of expansions (digital, analog I/Os...), up to 50 I/Os

Smart Compact

The easiest logic controller to implement, to program and to use on the market

Essential

The right product to tackle simple applications that still require a powerful logic controller



Smart Expandable



Smart Compact



Essential

Application example

Access Control

Millenium 3 offers both standard and customized product solutions for a range of applications, including automatic barriers, automatic doors, turnstiles, sectional doors and disabled access ramps.

em4 soft

The most intuitive programming software on the market

em4 web

Provides powerful application and device management



em4 remote



em4 alert



em4 local

* Network-compatible 2G/3G.

Application example

Water treatment

With the capability to manage pump circulation, monitor liquid levels, and measure the temperature and conductivity of water, em4 can help you take your application to the next level.

M3 soft

The M3 Soft is a high-performance software platform used to program the Millennium 3 logic controller and optimize design times.

Digital expansions
(up to 50 I/Os) & analog
(0-10V, 4-20mA, Pt100)



50 I/Os
0-10V
4-20mA



Modbus RTU and
Modbus TCP/IP
expansions



Additional application
specific functions (autotuning
PID, astronomical clock, ...)

Direct connection of NTC
temperature probes and LDR
luminosity sensors



Enhanced visibility on the
display with high contrast,
blue back lit LCD screen



Extended temperature
range (-20 °C to +70 °C)



Powerful and
cost effective



Bluetooth® connection
accessory for all the range for
applications that are complex
in terms of access



WHICH SOLUTION DO YOU NEED?

The Millenium 3 logic controller and the **em4** nano-PLC are the easiest to use programmable modules for various applications. With simple and intuitive software, controlling and monitoring of machines and automation installations is incredibly simple.



Millenium 3 Smart Expandable

Offers a large variety of expansions (digital, analog I/Os...), up to 50 I/Os

- › Expandable versions: 10 I/Os and 26 I/Os
- › With or without display, in 24 V $\overline{\text{--}}$, 12 V $\overline{\text{--}}$, 24 V $\sim$ and 100 $\rightarrow$ 240 V $\sim$ versions



Multiple configuration options derived from an extensive product range with numerous accessories

Millenium 3 toolbox

M3 soft

50 I/Os	Digital expansions up to 50 I/Os		Highly visible blue LCD
0-10V 4-20mA	Analog 0-10V, 4-20 mA, Pt100 expansions		Direct connection of NTC temperature probes
	Modbus RTU and Modbus TCP/IP expansions		Additional application specific functions
			Extended temperature range (-20 °C to +70 °C)
			Bluetooth® connection accessory



Millenium 3 Smart Compact

The easiest logic controller to implement, to program and to use on the market

- › Compact versions: 12 I/Os and 20 I/Os
- › With or without display, in 24 V $\overline{\text{--}}$, 12 V $\overline{\text{--}}$, 24 V $\sim$ and 100 $\rightarrow$ 240 V $\sim$ versions



Application-specific solutions thanks to dedicated and easy to use specific function blocks

Millenium 3 toolbox

M3 soft

	Highly visible blue LCD
	Direct connection of NTC temperature probes
	Additional application specific functions
	Extended temperature range (-20 °C to +70 °C)
	Bluetooth® connection accessory



Millenium 3 Essential

The right product to tackle simple applications that still require a powerful logic controller

- › Compact versions: 12 I/Os and 20 I/Os
- › Expandable versions: 10 I/Os and 26 I/Os
- › With or without display, in 24 V $\overline{\text{--}}$, 12 V $\overline{\text{--}}$ versions



The Millenium 3 Essential range is the cost effective solution for simple applications

Millenium 3 toolbox

M3 soft

	Powerful and cost effective
50 I/Os	Digital expansions up to 50 I/Os
0-10V 4-20mA	Analog 0-10 V, 4-20 mA, Pt100 expansions
	Modbus RTU and Modbus TCP/IP expansions
	Simplified Bluetooth® connectivity



em4 remote

The first all-in-one solution to bring your application into the Internet of Things

- › First PLC capable of fleet management including map localisation
- › Highly secured solution, using e-banking practices and infrastructure
- › Expandable from: 26 I/Os up to 46 I/Os



SIM card (2G version) & remote management subscription included for one year (em4 web, em4 app)



Machine / Equipment fleet management



Advanced event management



Secured platform and connections



Advanced data history



Device maintenance & management



Advanced monitoring and control functions



Map localization



Advanced remote services for your customers



Automatic clock synchronization



Customizable web interface



em4 toolbox

em4 soft

em4 web



em4 alert

Nano-PLC that can alert you via SMS and email

- › Needs only GSM network to operate (SMS)
- › Secured solution, only users identified in the PLC can interact
- › Expandable from: 26 I/Os up to 46 I/Os



* Compatible réseau 2G/3G.



No need to perform complicated integration between the PLC and a modem/gateway



Event management via SMS and email



Monitoring and control functions via SMS



Data report via SMS and datalogs via email or FTP



PLC to PLC SMS communication



Remote application program update



Remote directory management

em4 toolbox

em4 soft

em4 local/ethernet

The em4 for stand alone use or local area network

- › The most compact and powerful of its category
- › Includes highly accurate 4-20 mA analog inputs for industrial sensors
- › Expandable from: 26 I/Os up to 46 I/Os



Easily swap from one version to another version (remote and alert), enabling the upgrade of the equipment



PLC with local functions only



Modbus RS485 slave option interface



Embedded configurable 0-10V/4-20 mA accurate analog inputs



The most intuitive graphical function block language



Modbus TCP/IP client and server

em4 toolbox

em4 soft

SELECT YOUR CONTROLLER

Our products are specifically suited for integration in a wide range of applications.

Millenium3

- Highly visible blue LCD with 4 lines of 18 characters and configurable backlighting
- Allow the use of the entire library of specific function blocks in the software workshop
- Extended temperature range (-20 °C to +70 °C)
- Analog inputs 0-10 V $\sim$, Potentiometer, NTC, LDR (0-20 mA/Pt100 with converters)

Smart



Essential



em4

- Save time designing your application and remote functions using the most intuitive graphical function block language on the market
- Accurately measure your high end industrial sensors with the embedded configurable analog inputs (including 4-20 mA)
- Easily integrate one of our three high tech designs in your machine
- Adapt your application during its lifecycle thanks to the enhanced controlling performances


Glossy black



	Millenium 3 range	em4 range
Power Supply	12 V $\sim$, 24 V $\sim$ 24 V $\sim$, 100 $\rightarrow$ 240 V $\sim$	24 V $\sim$
Highly Visible HMI	Blue (Smart) or Green (Essential)	Black on white / white on black
Versions	Compact versions: 12 and 20 I/Os Expandable versions: 10 and 26 I/Os up to 50 I/Os	Expandable version: 26 I/Os up to 46 I/Os
Inputs on the base	Digital, High speed 6kHz Analog 0-10V 5%, Potentiometer, NTC, LDR	Digital, High speed 60kHz Analog 0-10 V, 4-20 mA 1%, Potentiometer, NTC, LDR
Outputs on the base	Relays 8 A or 5 A Static Digital or PWM	Relays 8 A or 6 A Static Digital or PWM
Inputs on expansions	Digital Analog 0-10V 2% 4-20 mA 1% PT100 1,5°C	Digital Analog 0-10 V 1% 4-20 mA 1%
Outputs on expansions	Relay 8 A or 5 A 0-10V 5% Static Digital or PWM	Relay 8 A or 6 A 0-10 V 1% 4-20 mA 1% Static Digital or PWM
Programming interface	USB cable	USB interface Ethernet port Remote download
Ethernet /Com	Ethernet Modbus TCP/IP (server) Modbus RS485 (slave) on expansion	Ethernet version: on base (Modbus TCP/IP server & client) Wireless 2G and 3G versions
Interface	USB, Bluetooth, memory, RS232	USB, Modbus RS485 (slave)
Programming language	FBD/SFC or LD 400 Function Blocks 200 Ladder lines	FBD/SFC 1000 Function Blocks
Temperature range	-20 °C +55 °C (Essential range) -20 °C +70 °C (Smart range)	-20 °C +60 °C
Real time clock backup	10 years	

COMPLETE YOUR EXPERIENCE!

Sensors, power supplies, converters, remote screens and communication accessories offer solutions to control your automation systems with the greatest ease of use.



MOST INTUITIVE PROGRAMMING SOFTWARE ON THE MARKET

Simple

- › Quick, simple and intuitive programming which does not require specialist knowledge
- › Self-teaching made easier thanks to a user-friendly online help guide and programming examples
- › A simulation mode that consistently represents controller operation

Powerful

- › A complete range of more than 100 function blocks
- › All basic functions: counting, timing, comparison, display, logic, gain, sin/cos, etc. are also available
- › A wide range of dedicated functions: pump rotation, PID regulation, movement, pressure, level, water ratio, solar tracking, and flow

User-friendly and ergonomic

- › Software available in 5 languages: English, French, Italian, German and Spanish
- › Function block programming is fun and very visual
- › Programming languages:
 - FBD (Function Bloc Diagram)
 - SFC (Sequential Function Chart/Grafcet)
 - LD (Ladder Diagram) only on M3 soft

User-definable and effective


- › Possibility of creating and saving custom macros allowing the user to simplify programs
- › Possibility of locking macros with a password for greater security

M3 SOFT

M3 Soft is the easiest programming software to use on the market. It is also incredibly powerful and user-friendly. Thanks to the most comprehensive library of application-specific function blocks in the industry, it allows you to customise your applications.



M3 soft
Function blocks



em4 SOFT

4

em4 soft integrates all the remote management features in a single tool. Based on our strong experience in Millenium programming software development, em4 soft is the new easy-to-use programming tool dedicated to em4.

em4 soft Function blocks




Event

Allows up to 24 events
SMS/email messages including 2
attached analog values



Data Logging

Allows up to 3 blocks of 8 values
to be logged at a specified time
interval or on command signal



Monitoring

Allows easy remote
monitoring and control of
your application

32 bit function blocks

Allows high speed
count, tachometer,
power management,
calculation with
32 bit values



Display

Large 4x18 character
display allows user to
visualize text, status,
times and control values in
the program




PID Regulator

Will interface with water
booster drives for pressure
needs based on demand



Sunset / Sunrise

Calculate the sunrise and
sunset time




em4 WEB

With em4 remote, your equipment gets the simplest access to the Internet of Things

- The **em4 web** provides you with a powerful **device management** web-based platform.
- There is no need to configure the communication: log on, identify your **em4** remote and instantly get connected!
- It allows you to easily manage your **em4** fleet on demand:
 - manage your access rights, as well as your customers
 - **download** your application program or firmware
 - **monitor** and control your devices
 - **locate** them on a map
 - display your **data history**
 - receive **event notifications** by email and SMS

Last but not least, it implements the latest security systems and protocols.

Map localisation



Your em4 fleet available anywhere, anytime

Download your software:



Download
M3 soft



Download
em4 soft

MAKE UP YOUR OWN SOLUTION

MILLENIUM 3 RANGE

						Availability/Compatibility				
Type		Part number	Supply	Inputs	Outputs	12 V $\cdots$	24 V $\cdots$	Solid State Output 0.5 A/PWM	Essential version **	
M3 Smart kits 	Kit 12 Smart*	88 974 080	24 V $\cdots$	8 (4 configurable as analog)	4 relays 8 A					
	Kit 12 Smart*	88 974 081	100 $\rightarrow$ 240 V $\sim$	8	4 relays 8 A					
	Kit 20 Smart*	88 974 082	24 V $\cdots$	12 (6 configurable as analog)	8 relays 8 A					
	Kit 20 Smart*	88 974 083	100 $\rightarrow$ 240 V $\sim$	12	8 relays 8 A					
	Kit 26 Smart*	88 974 084	24 V $\cdots$	16 (6 configurable as analog)	8 relays 8 A and 2 relays 5 A					
	Kit 26 Smart*	88 974 085	100 $\rightarrow$ 240 V $\sim$	16	8 relays 8 A and 2 relays 5 A					
Compact versions										
 With display	CD12 Smart*	88 974 041	24 V $\cdots$	8 (4 configurable as analog)	4 relays 8 A	✓		✓	✓	
	CD12 Smart*	88 974 043	100 $\rightarrow$ 240 V $\sim$	8	4 relays 8 A		✓			
	CD20 Smart*	88 974 051	24 V $\cdots$	12 (6 configurable as analog)	8 relays 8 A	✓		✓	✓	
	CD20 Smart*	88 974 053	100 $\rightarrow$ 240 V $\sim$	12	8 relays 8 A		✓			
	 Without display	CB12 Smart*	88 974 021	24 V $\cdots$	8 (4 configurable as analog)	4 relays 8 A	✓			✓
		CB12 Smart*	88 974 023	100 $\rightarrow$ 240 V $\sim$	8	4 relays 8 A		✓		
CB20 Smart*		88 974 031	24 V $\cdots$	12 (6 configurable as analog)	8 relays 8 A				✓	
CB20 Smart*	88 974 033	100 $\rightarrow$ 240 V $\sim$	12	8 relays 8 A		✓				
Expandable versions										
 With display	XD10 Smart*	88 974 141	24 V $\cdots$	6 (4 configurable as analog)	4 relays 8 A	✓		✓	✓	
	XD10 Smart*	88 974 143	100 $\rightarrow$ 240 V $\sim$	6	4 relays 8 A		✓			
	XD26 Smart*	88 974 161	24 V $\cdots$	16 (6 configurable as analog)	8 relays 8 A and 2 relays 5 A	✓		✓	✓	
	XD26 Smart*	88 974 163	100 $\rightarrow$ 240 V $\sim$	16	8 relays 8 A and 2 relays 5 A		✓			
	 Without display	XB10 Smart*	88 974 131	24 V $\cdots$	6 (4 configurable as analog)	4 relays 8 A	✓		✓	✓
		XB10 Smart*	88 974 133	100 $\rightarrow$ 240 V $\sim$	6	4 relays 8 A		✓		
XB26 Smart*		88 974 151	24 V $\cdots$	16 (6 configurable as analog)	8 relays 8 A and 2 relays 5 A	✓		✓	✓	
XB26 Smart*	88 974 153	100 $\rightarrow$ 240 V $\sim$	16	8 relays 8 A and 2 relays 5 A		✓				
With Removable Terminal Blocks										
	CD12 RBT Smart*	88 974 441	24 V $\cdots$	8 (4 configurable as analog)	4 relays 8 A					
	XD26 RBT Smart*	88 974 561	24 V $\cdots$	16 (6 configurable as analog)	8 relays 8 A and 2 relays 5 A					
Sandwich extensions										
 Communication	XN05 Modbus TCP/IP	88 970 270	24 V $\cdots$						✓	
	XN06 Modbus RS485	88 972 250	24 V $\cdots$						✓	
	XN07 Master RS485	88 974 250	24 V $\cdots$							
 Digital	XE10	88 970 321	24 V $\cdots$	6	4 relays 5 A				✓	
	XE10	88 970 323	100 $\rightarrow$ 240 V $\sim$	6	4 relays 5 A		✓		✓	
Termination Extensions										
 Digital	XR06	88 970 211	24 V $\cdots$	4	2 relays 8 A	✓			✓	
	XR06	88 970 213	100 $\rightarrow$ 240 V $\sim$	4	2 relays 8 A		✓		✓	
	XR10	88 970 221	24 V $\cdots$	6	4 relays 8 A	✓			✓	
	XR10	88 970 223	100 $\rightarrow$ 240 V $\sim$	6	4 relays 8 A		✓		✓	
	XR14	88 970 231	24 V $\cdots$	8	4 relays 8 A and 2 relays 5 A	✓			✓	
	XR14	88 970 233	100 $\rightarrow$ 240 V $\sim$	8	4 relays 8 A and 2 relays 5 A		✓		✓	
 Analog	XA03 3xPt100	88 970 800	24 V $\cdots$	3 analog (Pt100)						
	XA04 2AI/2AO	88 970 241	24 V $\cdots$	2 analog 0-10 V/0-20 mA (1 Pt100)	2 analog 0-10V/PWM				✓	
Bare board and resin board versions										
 Bare board	NB12	88 970 001	24 V $\cdots$	8 (4 configurable as analog)	4 relays 8 A	✓				
	NB12	88 970 003	100 $\rightarrow$ 240 V $\sim$	8	4 relays 8 A					
	NB20	88 970 011	24 V $\cdots$	12 (6 configurable as analog)	8 relays 8 A					
	NB20	88 970 013	100 $\rightarrow$ 240 V $\sim$	12	8 relays 8 A					
 Resin board	NBR12	88 973 001	24 V $\cdots$	8 (4 configurable as analog)	4 relays 8 A	✓		✓		
	NBR26	88 973 061	24 V $\cdots$	16 (6 configurable as analog)	10 relays 8 A	✓		✓		
	NBR32	88 973 211	24 V $\cdots$	20 (6 configurable as analog)	12 relays 8 A	✓				
	NBR40	88 973 231	24 V $\cdots$	24 (6 configurable as analog)	16 relays 8 A	✓				

* Millennium 3 Smart: backlit blue LCD display. Extended operating temperature range and function block library

**Millennium 3 Essential: Logic Controller with green screen and industrial temperature range

MILLENIUM 3 ACCESSORIES

Power supplies and DC/DC converters in modular casings

	Part number	Input Voltage	Output voltage	Nominal power	Output current
	88 950 303	100 → 240 V~	24 V~	7.5 W	0.3 A
	88 950 304	100 → 240 V~	24 V~	15 W	0.6 A
	88 950 307	100 → 240 V~	24 V~	30 W	1.2 A
	88 950 302	100 → 240 V~	24 V~	60 W	2.5 A
	88 950 305	100 → 240 V~	5 V~	20 W	4 A
	88 950 306	100 → 240 V~	12 V~	24 W	2 A
	88 950 320	9,2 → 18 V~	12 V~	10 W	0.8 A
	88 950 321	9,2 → 36 V~	24 V~	6 → 10 W	0.4 A

Connection accessories, tools and programming software

	Part number	Description
	88 970 111	M3 Soft: Millenium 3 programming software (CD-ROM)
	88 970 108	Memory cartridge for transfer and saving of programs
	88 970 102	3 m serial link cable: PC DB9 F → Millenium 3
	88 970 104	Millenium 3 → Bluetooth® interface (class A 10 m)
	88 970 109	3 m USB link cable: PC → Millenium 3
	88 970 110	Bluetooth® adaptor → USB (class A 10 m)
	88 970 123	1.80 m serial link cable: DB9 M/DB9 F
	88 970 510	0.5 m serial link cable: Millenium 3 → DB9 M
	88 974 106	Ready to use Millenium 3 Smart democase including: - a CD12 Smart, a CTN probe, a LDR probe, an I/O simulator - a 3 m USB link cable: PC → Millenium 3, a M3 Soft CD - a power supply 110-230 V~

Millenium 3 Virtual Display



Android smartphone and tablet as well as Windows XP/7 PC application

Man/Machine interface



TFT-LCD compact 4.3" and 7" resistive touch panels - MTP6/50, MTP8/50 & MTP8/70

Plug & Play remote LCD displays/keypads

Remote LED display - Input 0-10 V

Temperature probes and light sensors



NTC Temperature probes

LDR Light sensors

0-10 V Temperature sensors

Temperature probes Pt100 & Thermocouple

Temperature and signal converters



Thermocouple Pt100/Pt1000 → 0-10 V

PWM to 0-10 V/4-20 mA to 0-10 V

Other accessories and kits



Standard Smart and Essential product kits

Removable connectors

Potentiometer Ø 22 mm

Faceplates



Check out the
Millenium 3 datasheets!

em4 RANGE

		Connection type							
Product description						Glossy black	Details		
Bases							Common characteristics:		
	em4 remote 2G*		✓			88 981 153	- Supply: 24V--- - Inputs: 16 digital inputs (including 4 high speed, 8 analog 0-10 V / potentiometers and 4 analog 0-10 V / 4-20 mA) - Outputs: 10 digital outputs (including 2 static 0.5 A PWM, 2 relays 6 A and 6 relays 8 A)		
	em4 alert 2G		✓			88 981 113			
	em4 alert 3G			✓		88 981 123			
	em4 local	✓				88 981 103			
	em4 Ethernet				✓	88 981 133			
Starter kits							An em4 starter kit includes:		
	Starter kit em4 remote 2G*		✓			88 981 156	- The em4 remote nano-PLC - The standard 3 m antenna	- The USB interface - The USB programming cable	- The em4 soft (USB key)
	Starter kit em4 alert 2G		✓			88 981 116	- The em4 alert nano-PLC - The standard 3 m antenna	- The USB interface - The USB programming cable	
	Starter kit em4 alert 3G			✓		88 981 126			
	Starter kit em4 local	✓				88 981 106	- The em4 local nano-PLC		
	Starter kit em4 Ethernet				✓	88 981 136		- The Ethernet cable	
Evaluation cases							The ready-to-use evaluation case includes:		
	Evaluation case em4 remote 2G*		✓			88 980 185	- The starter kit (description above) - The power supply 110-230 Va with Europe and US adaptor - The simulator PCB for the 16 Inputs with switches, potentiometers and terminals to connect your sensor for evaluation - The simulator PCB for the 10 Outputs with 11 LEDs and terminals to connect the 2 static outputs to a device for evaluation		
	Evaluation case em4 alert 2G		✓			88 980 181			
	Evaluation case em4 alert 3G			✓		88 980 182			
	Evaluation case em4 local	✓				88 980 180			
	Evaluation case em4 Ethernet				✓	88 980 183			

* em4 remote 2G, include the first year of subscription to em4 remote access (em4 web & em4 app), with a SIM card.

Product description	Inputs	Outputs	Glossy black
Expansions			
em4 digital expansion E10R	6 digital inputs (configurable as analog 0-10 V or potentiometer)	4 digital outputs (2 relays 6 A and 2 relays 8 A)	88 982 113
em4 analog expansion E10A	6 digital inputs (configurable as analog 0-10 V / 4-20 mA)	4 outputs (2 static 0.5 A PWM and 2 analog 0-10 V)	88 982 213

Product description			Description		
Part number			Key features		
			Part number		
Interfaces	em4 USB interface black	88 980 110	Programmable touch panels		
	em4 interface RS485 Modbus slave black	88 980 120	MTP6/50 user kit*	- 4.3" color touch panel - Modbus RS232/RS485 serial port - USB port	88 970 492
Accessories	em4 Set of I/O simulator for bases	88 980 150	MTP8/50 user kit*	- 4.3" color touch panel - Modbus RS232/RS485 serial port - Ethernet TCP/IP port	88 970 494
	Antenna 3 m standard	88 980 160	Cable em4-MTP6/50 & MTP8/50	For use with em4 interface RS485 Modbus interface (88 980 120)	88 980 171
	Antenna 3 m int/ext flat	88 980 161	MTP8/70 user kit*	- 7" color touch panel - 2x Modbus RS232/RS485 serial port - USB port, Ethernet TCP/IP port	88 970 496
	Antenna 10 m ext	88 980 162	Cable em4-MTP8/70	For use with em4 interface RS485 Modbus (88 980 120)	88 980 172
	USB cable 3 m B type	88 980 170	MTP6/50 - MTP8/70 programming kit (USB)	- USB - Mini USB cable - EB Software (CD)	88 970 501
	em4 soft (USB key)	88 980 140	MTP6/50 - MTP8/70 programming kit (Ethernet)	- Ethernet crossover cable - EB Software (CD)	88 970 502
Power supplies	Modular power supply 24 V--- 7.5 W	88 950 303			
	Modular power supply 24 V--- 15 W	88 950 304			
	Modular power supply 24 V--- 30 W	88 950 307			
	Modular power supply 24 V--- 60 W	88 950 302			

* em4 cable not included in User Kit

PERFECTLY MATCH ALL OF YOUR REQUIREMENTS

Crouzet has identified six major applications for which Millenium 3 and em4 are particularly suitable:



ACCESS CONTROL

Control opening and closing of doors. Allow or restrict access with automatic detection, on a timer, or on certain days/time.



TEMPERATURES

Management of various parameters such as heating, cooling, fluid temperatures, operation, calendar-based function, frost protection mode, alarm management, etc.




WATER TREATMENT

Managing circulation pumps, monitoring levels, temperature and conductivity of the water. Irrigation control based on temperature, humidity, and day/night cycle



SMALL INDUSTRIAL MACHINES

Controlling the motor that unrolls the packing film. Controls cutting of the film after heat sealing and monitors the duration of the motor cycles. Controlling heat sealing times on blister packs, packaging bags, etc.



SOLAR WATER HEATING

Automation of operation and heating regulation, remote management of the installation.



LIGHTING

Managing flashing on illuminated signs

AMERICAS
CANADA

Tel.: +1 (855) 929-5465
americas.custserv@crouzet.com

MEXICO

Tel.: +1 (855) 929-5465
americas.custserv@crouzet.com

USA

+1 (855) 929-5465
americas.custserv@crouzet.com

COUNTRIES NOT LISTED

+1 (855) 929-5465
americas.custserv@crouzet.com

EUROPE / MIDDLE EAST / AFRICA
BELGIUM

Tel.: +32 (0) 2 620 06 05
Fax: +32 (0) 2 461 00 23
klantenservice@crouzet.com

FRANCE

Tel.: +33 (0) 475 802 101
Fax: +33 (0) 475 828 900
relationclient@crouzet.com

GERMANY / AUSTRIA

Tel.: +49 (0) 2103/9385930
Fax: +49 (0) 2103/980-222
kundenservice@crouzet.com

ITALY

Tel.: +39 (02) 38 594 099
Fax: +39 (02) 82 952 104
assistenzaclienti@crouzet.com

SPAIN / PORTUGAL

Tel.: +34 (91) 215 80 95
Fax: +34 (93) 2 20 02 05
atencionalcliente@crouzet.com

SWITZERLAND

Tel.: +41 (0) 225 67 57 90
Fax: +41 (0) 565 88 02 75
kundenservice@crouzet.com

THE NETHERLANDS

Tel.: +31 (0) 20-654 52 20
klantenservice@crouzet.com

UNITED KINGDOM

Tel.: +44 (0) 2076 600 025
customer.relation@crouzet.com

COUNTRIES NOT LISTED

Tel.: +33 (0) 475 802 102
Fax: +33 (0) 475 828 900
customer.relation@crouzet.com

ASIA / PACIFIC
CHINA

Tel.: +86 (21) 8025 7166
Fax: +86 (21) 6107 1771
china@crouzet.com

INDIA

Tel.: +91 (80) 4113 2204/05
Fax: +91 (80) 4113 2206
india@crouzet.com

SOUTH KOREA

Tel.: +82 (2) 2679 8312
Fax: +82 (2) 2679 9888
korea@crouzet.com

EAST ASIA PACIFIC

Tel.: +86 (21) 8025 7177
Fax: +86 (21) 6107 1771
eap@crouzet.com

Warning:

The product information contained in this catalogue is given purely as information and does not constitute a representation, warranty or any form of contractual commitment. Crouzet Automatismes SAS and its subsidiaries reserve the right to modify their products without notice. It is imperative that we should be consulted over any particular use or application of our products and it is the responsibility of the buyer to establish, particularly through all the appropriate tests, that the product is suitable for the use or application. Under no circumstances will our warranty apply, nor shall we be held responsible for any application (such as any modification, addition, deletion, use in conjunction with other electrical or electronic components, circuits or assemblies, or any other unsuitable material or substance) which has not been expressly agreed by us prior to the sale of our products.